

HIGHGLIDE

Aloe Lube

Incorporated

Protect Well Productivity

Aloe Lube's HIGHGLIDE™ premium glycol-based lubricant reduces torque and drag, and increases rate of penetration.

During the drilling process, torque, drag, bit-balling, sloughing and shale swelling cause costly and time-consuming problems, including shutdowns. Aloe Lube's glycol-based HIGHGLIDE lubricant helps protect well productivity and prevent these problems by:

- significantly reducing torque & drag and bit-balling increasing rate of penetration in all formations
- forming a hydrostatic barrier between the drill pipe and the sidewall and inhibiting shales
- increasing effectiveness during horizontal drilling when used in combination with Gilsonite

HIGHGLIDE lubricant is dispersible in all types of water-based fluids and will not interfere with rheological properties. Recommended concentrations range from 2 to 5% for most applications.

Available in bulk, 275 gallon totes and 55 gallon drums.



BENEFITS:

- Significantly reduces torque and drag
- Reduces pick-up and slack weight
- Helps prevent bit-balling
- Increases ROP
- Cost Effective
- Will not grease out
- Low toxicity

SPECIFICATIONS

Appearance	Light to dark amber
Physical Form	Viscous liquid, mild odor
Specific Gravity	1.04 - 1.13 @ 25° C
Solubility in Water	Water Dispersible
Flash Point	380° F / 193° C

Protect well productivity with Aloe Lube's BLACKMAX glycol-based lubricant.



(361) 575-0542



aloelubeinc.com

HIGHGLIDE is a trademark of Aloe Lube, Inc. © 2018. All rights reserved. This product is sold without warranty either express or implied of merchantability or fitness for purpose and upon condition that purchaser make its own tests to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product.